



WITH ANTI-COLLISION SYSTEM

TOWABLE PAX STEP

Towable pax step has various type i.e for passenger boarding, for interior cleaning/maintenance or for cargo aircraft used. It is divided into 2 models as follow:-

- 1) APS 3700 for narrow body aircraft
- 2) APS 5800 for all type of aircraft

It was design to be robust at the highest stability. All side panel are using perforated sheet in order to reduce wind force from side body.



SAFETY

- Chequer plate or abrasive floor surface to prevent slippage.
- Automatic lock on the platform riser.
- 4 point stabilizer jack for stability.
- LED lamp at the stair and platform by solar power.



SPECIFICATION

	APS 3700	APS 5800
Dimension	6600 (L) x 2325(W) 3050(H)	8490 mm(L) x 2425mm(W) 4410mm (H)
Platform Size	1500(W) x 1400(L) Optional 2500(W) x 1700(L)	1500(W) x 1400(L) Optional 2500(W) x 1700(L)
Min-Max Platform Reach	Min 2100 Max 3750	Min 3200 Max 5800
Gross Weight	1500kg	2000kg
Platform Adjustment	Hydraulic cylinder actuated by handpump	Hydraulic cylinder actuated by handpump
Lock	Automatic spring plunger	Automatic spring plunger
Stair width	1200mm	1200mm
Stair depth	290mm	290mm
Tyre	Solid tyre 4.00 x 8	Solid tyre 4.00 x 8
Stabilizer	4 point	4 point
Tow speed	25 km/h	25 km/h

*All dimension in mm

APPLICABLE AIRCRAFT

APS 3700

Only for narrow body aircraft

B727, B737, A300, A310, A320, A321

APS 5000

For all narrow body and wide body aircraft

B727, B737, B747, B757, B767, B787

A300, A310, A320, A330, A340, A350, A380

IATA COMPLIANCE

AHM 904, AHM 910, AHM 915, AHM 916, AHM 920A



AGRIQUIP

AGRIQUIP MACHINERY SDN BHD
(Reg No. 612132-A)

Factory & Office Address :

Lot 5936, Jalan Salak Tinggi / Banting, RTB Bukit Changgang,
42700 Banting, Selangor Darul Ehsan, MALAYSIA.